

Technical Data VSPC

Product Specifications

Medecor
floors by EHEINDUSTRY
 HARDWOOD FLOORING

HARDWOOD FLOORING

Product Details

Technical Data		Technical Data	
Type	Wood Veneer SPC Plank	Installation Method	Click System
Veneer Thickness	0.6mm; 1.2mm	Protective Coating	UV coating
Rigid Core Thickness	4.5mm; 5.0mm	Backing PAD	Without
Dimensions	1220mm(L)x125mm(W)	Surface	Woodgrain
Planks per Box	10	Profile	Micro Bevel
Sq.m per Box	1.53sq.m	Sq.m per Pallet	99.13sq.m

Performance

UV coating			5 undercoat,2 finished coat
Peeling Strength of layers	Pass		EN 431
Shearing force of layers	Good		EN 433
Residual indentation after static load	Mean value 0.01mm		EN 432
Dimension Stability	Shrinkage ≤ 0.02%; Curling ≤ 0.07mm		EN 424
Flexibility -10mm mandrel	No damage		EN 435
Resistance to chemicals	Class sero		EN 423
Bearing a castor chair	No disturbance, no delamination		EN 425
Color fastness to light	≥6		ISO 105 B02
Wear resistance	Pass		EN 660
Resistance to fire	NFPA CLASS B		
Slip resistance	R10		
Performance classification	23,34,43		
GB/T4085 GB/T4085 PVC block material performance testing GB 8624 B1 grade flammability testig	Pass		
CNS 8907 anti-flaming testing	Pass		